

Original Research

Received 28 Jan 2026

Revised 11 April 2026

Accepted 02 May 2026

International Revista of
Computer, Civil, Electronics,
Electrical, Mechanical
Engineering 2026;
Vol. 1 No. 1: 28–44

KEYWORDS:

CNC Technology, Precision
Manufacturing, Multi-Axis
Machining, High-Speed Machining,
Adaptive Control, Digital Twin,
Tool-Condition Monitoring,
Artificial Intelligence, CAD/CAM
Integration, Smart Manufacturing,
Process Automation, Industrial
Metrology.

Advanced CNC Technologies for Precision Manufacturing

Dr. Aarav Veylan¹, Dr. Julian Ardent², Dr. Helena Morcant³,
Dr. Nora Veymont⁴

¹ Associate Professor, Department of Mechanical and Manufacturing Engineering, Northbridge Institute of Civic Studies, Sydney, Australia.

² Senior Researcher, Centre for Intelligent Manufacturing Systems, Stonebridge Futures Institute, London, United Kingdom.

³ Assistant Professor, Department of Mechatronics and Industrial Automation, Evermont Civic Research Center, Toronto, Canada.

⁴ Research Fellow, Department of Precision Engineering and Digital Manufacturing, Bluecrest Social Observatory, Madrid, Spain.

ABSTRACT: Computer Numerical Control technology has transformed manufacturing by enabling automated, repeatable and accurate production of geometrically complex components. Modern CNC systems extend beyond conventional programmed machining through multi-axis motion, high-speed machining, intelligent process monitoring, adaptive control, digital twins, artificial intelligence, industrial robotics and networked manufacturing. These technologies are particularly important in aerospace, automotive, biomedical, electronics, defence and tool-and-die industries, where components require tight dimensional tolerances and high surface quality. Nevertheless, precision CNC manufacturing is affected by thermal deformation, tool wear, chatter, spindle errors, fixture deformation, geometric inaccuracies and variations in material properties. This review-based article examines advanced CNC technologies and their contribution to precision, productivity, flexibility and process reliability. It discusses five-axis machining, high-speed cutting, direct-drive systems, intelligent controllers, sensor-based monitoring, adaptive machining, digital twins, machine learning, automated inspection and cyber-physical production. A conceptual framework connecting machining parameters, system errors and product quality is presented. The study finds that advanced CNC technologies can significantly improve manufacturing performance when supported by accurate calibration, process planning, sensor integration, data interoperability and skilled personnel. Future CNC development will increasingly focus on autonomous parameter optimization, closed-loop quality control, human-machine collaboration and self-correcting production systems.

1. Introduction

Precision manufacturing involves producing components within narrowly specified dimensional, geometric and surface-quality limits. Industries such as aerospace, medical devices, semiconductors, automotive engineering and defence require components capable of operating under demanding mechanical, thermal and environmental conditions.

Computer Numerical Control machines use programmed numerical instructions to control tool and workpiece motion. A conventional CNC programme defines coordinates, feed rates, spindle speeds, tool changes and auxiliary operations. Compared with manual machines, CNC systems provide:

- Greater positioning accuracy

- Improved repeatability
- Higher productivity
- Reduced operator dependence
- Complex contour generation
- Automated tool changing
- Consistent product quality
- Easier production-data collection
- Integration with computer-aided manufacturing

Modern manufacturing demands exceed the capabilities of basic three-axis CNC machines. Complex free-form surfaces, thin-walled components, difficult-to-machine materials and micrometre-level tolerances require advanced motion systems, sensors, software, control algorithms and metrology.

Advanced CNC manufacturing combines mechanical accuracy with digital intelligence. The machine no longer operates only as a programmed motion device; it becomes a connected cyber-physical system capable of monitoring, predicting and adjusting its own performance.

2. Objectives of the Study

The principal objectives are:

1. To explain the development of advanced CNC technologies.
2. To identify the main factors affecting machining accuracy.
3. To examine multi-axis, high-speed and intelligent machining systems.
4. To analyse sensor-based monitoring and adaptive control.
5. To evaluate applications of artificial intelligence and digital twins.
6. To discuss automated inspection and error-compensation methods.
7. To identify implementation challenges and future research directions.

3. Research Methodology

The study adopts a descriptive and analytical literature-review methodology. Research concerning CNC systems, manufacturing automation, machine-tool errors, process monitoring, artificial intelligence, digital twins and precision metrology has been examined.

The analysis covers:

- Machine configuration
- Motion-control technology
- Machining-process mechanics
- Tool and spindle condition
- Thermal and geometric errors
- Sensors and data acquisition
- Artificial intelligence

- Digital manufacturing
- Quality inspection
- Cybersecurity and interoperability

The article does not claim to report a new machining experiment. Numerical performance depends on the machine, material, tool, process parameters and environmental conditions.

4. Development of CNC Technology

Early numerical-control systems used punched tapes to provide motion commands. Contemporary CNC systems employ digital processors, high-resolution feedback devices and network communication.

Manufacturing stage	Principal characteristics
Manual machining	Operator-controlled tool movement
Numerical control	Predefined instructions through physical media
Computer numerical control	Computerized programme storage and execution
Distributed numerical control	Central management of multiple machines
Computer-integrated manufacturing	Integration with design and production systems
Smart CNC	Sensors, analytics and network connectivity
Autonomous machining	Real-time prediction, optimization and self-correction

The development of CNC technology reflects a movement from fixed automation toward flexible and intelligent production.

5. Principal Components of an Advanced CNC System

An advanced CNC machine contains several interdependent subsystems.

5.1 Machine-control unit

The controller interprets the part programme, calculates tool trajectories and sends commands to the drive system. Modern controllers support high-speed interpolation, look-ahead functions, tool compensation and real-time data communication.

5.2 Drive and feedback system

Servo motors move the machine axes. Encoders and linear scales measure actual position and provide feedback to the controller.

The position error can be expressed as:

$$e_p(t) = x_r(t) - x_a(t)$$

Where:

- $e_p(t)$ = Position error
- $x_r(t)$ = Reference position
- $x_a(t)$ = Actual position

The control system continuously attempts to minimize this error.

5.3 Spindle system

The spindle holds and rotates the cutting tool or workpiece. Precision machining requires low vibration, minimal runout, thermal stability and appropriate speed–torque characteristics.

5.4 Tool-changing system

Automatic tool changers reduce non-productive time and allow several operations to be completed within one setup. Tool magazines may contain measuring probes and duplicate tools for automatic replacement.

5.5 Sensor and communication system

Sensors measure vibration, force, acoustic emission, temperature, spindle power, current, displacement and tool condition. Communication networks transfer data to controllers, monitoring platforms and manufacturing-execution systems.

6. Multi-Axis CNC Machining

Three-axis machines move along the X, Y and Z directions. Four- and five-axis systems introduce rotary axes that allow the tool or workpiece to approach the component from multiple orientations.

6.1 Advantages

Five-axis machining offers:

- Production of complex free-form surfaces
- Fewer workpiece setups
- Reduced fixture errors
- Improved tool accessibility
- Shorter cutting tools
- Better surface finish
- Reduced production time
- Machining of undercuts and inclined features

6.2 Applications

Multi-axis systems are widely used for:

- Turbine blades
- Aircraft structural components
- Impellers
- Medical implants
- Moulds and dies
- Automotive components
- Marine propellers
- Precision optical components

6.3 Technical challenges

The accuracy of multi-axis machining depends on the coordinated movement of linear and rotary axes. Small rotary-axis errors can produce large tool-position deviations.

Challenges include:

- Kinematic transformation

- Rotary-axis calibration
- Collision avoidance
- Post-processor accuracy
- Tool-centre-point control
- Singularities
- Complex fixture design
- Programme verification

7. High-Speed Machining

High-speed machining uses elevated spindle speeds and feed rates to remove material efficiently while maintaining acceptable forces and surface quality.

The material-removal rate in milling can be approximated as:

$$MRR = a_p \times a_e \times v_f$$

Where:

- MRR = Material-removal rate
- a_p = Axial depth of cut
- a_e = Radial width of cut
- v_f = Feed velocity

High-speed machining is useful for aluminium alloys, dies, moulds and thin-walled aerospace structures.

Advantages

- Higher material-removal rate
- Shorter production cycles
- Reduced cutting forces in selected conditions
- Improved surface quality
- Increased ability to machine thin walls
- Potential reduction in finishing operations

Limitations

- High spindle and tool cost
- Rapid tool wear
- Heat generation
- Chatter risk
- Complex process planning
- Demanding balancing requirements

- Increased need for programme look-ahead
- Safety risks from high rotational speed

The controller must process upcoming programme blocks rapidly to avoid sudden changes in velocity and acceleration.

8. Precision and Error Sources

The total machining error can be represented conceptually as:

$$E_T = E_G + E_T + E_S + E_D + E_W + E_F + E_C$$

Where:

- E_T = Total manufacturing error
- E_G = Geometric error
- E_T = Thermal error
- E_S = Spindle error
- E_D = Drive and control error
- E_W = Tool-wear error
- E_F = Fixture and workpiece deformation
- E_C = Cutting-process error

The notation uses the same symbol for total and thermal error in some engineering texts; for clarity, thermal error may alternatively be denoted E_{th} .

$$E_{total} = E_G + E_{th} + E_S + E_D + E_W + E_F + E_C$$

Major error sources

Error source	Example	Quality effect
Geometric error	Straightness or squareness deviation	Dimensional inaccuracy
Thermal error	Spindle and ball-screw expansion	Position drift
Tool wear	Flank wear or edge chipping	Size and surface variation
Vibration	Forced vibration or chatter	Waviness and poor finish
Fixture error	Incorrect location or deformation	Misalignment
Servo error	Following error or backlash	Contour deviation
Workpiece deformation	Cutting-force or thermal distortion	Form error
Programming error	Incorrect offset or tool path	Scrap or collision

9. Thermal-Error Compensation

Thermal errors are among the major contributors to machine-tool inaccuracy. Heat may originate from:

- Spindle bearings
- Motors and drives
- Ball screws

- Guideways
- Cutting processes
- Hydraulic systems
- Ambient-temperature variation

Thermal expansion can be approximated as:

$$\Delta L = \alpha L_0 \Delta T$$

Where:

- ΔL = Change in length
- α = Thermal-expansion coefficient
- L_0 = Initial length
- ΔT = Temperature change

Thermal-error control methods include:

- Machine warm-up cycles
- Temperature-controlled production areas
- Symmetrical machine structures
- Cooling and lubrication
- Low-expansion materials
- Temperature sensors
- Finite-element models
- Regression models
- Neural-network prediction
- Real-time controller compensation

Accurate compensation must remain reliable under different spindle speeds, workloads and ambient conditions.

10. Tool-Condition Monitoring

Tool wear affects dimensional accuracy, surface roughness, cutting force and productivity. Unexpected tool failure can damage the workpiece, fixture and spindle.

Monitoring variables

- Cutting force
- Spindle motor current
- Acoustic emission
- Vibration
- Sound
- Temperature

- Tool images
- Surface quality
- Power consumption

Monitoring approaches

Direct methods inspect the tool using cameras, microscopes, lasers or contact measurement. They can provide accurate wear information but may interrupt production.

Indirect methods estimate tool condition from process signals. They support real-time monitoring but require signal processing and reliable models.

A tool-monitoring system may classify the tool as:

- New
- Stable
- Progressively worn
- Near failure
- Broken

The system can then adjust parameters, issue an alarm or automatically load a replacement tool.

11. Chatter Detection and Suppression

Machining chatter is a self-excited vibration that produces poor surface quality, excessive noise and rapid tool wear. It can also damage the spindle or workpiece.

Chatter depends on:

- Spindle speed
- Depth of cut
- Tool geometry
- Workpiece stiffness
- Machine dynamics
- Tool overhang
- Material properties

Stability-lobe diagrams help identify combinations of spindle speed and depth of cut that permit stable machining.

Advanced systems detect chatter through vibration, acoustic emission, force or spindle-current signals. Corrective actions include:

- Adjusting spindle speed
- Reducing depth of cut
- Modifying feed rate
- Selecting a different tool
- Changing tool orientation

- Using variable-pitch cutters
- Applying active vibration control

12. Adaptive Control

Conventional CNC systems follow predefined parameters even when tool condition, material properties or cutting conditions change. Adaptive control modifies process parameters using real-time measurements.

A basic feedback relationship can be written as:

$$u(t) = f[F_c(t), V(t), T(t)P(t)W(t)]$$

Where:

- $u(t)$ = Control action
- $F_c(t)$ = Cutting force
- $V(t)$ = Vibration
- $T(t)$ = Temperature
- $P(t)$ = Power
- $W(t)$ = Estimated tool wear

The controller may change feed, speed, coolant supply or depth of cut to maintain a desired force, power, temperature or surface condition.

Benefits

- Prevention of tool overload
- Longer tool life
- Improved productivity
- Reduced scrap
- Better process stability
- Consistent surface quality

Limitations

- Sensor noise
- Control delay
- Model uncertainty
- Difficult process interactions
- Safety-validation requirements
- Integration with proprietary CNC systems

13. Artificial Intelligence in CNC Manufacturing

Artificial intelligence can identify complex relationships among machining parameters, sensor signals, tool condition and product quality.

Major applications

1. Tool-wear prediction
2. Chatter detection
3. Surface-roughness estimation
4. Cutting-force prediction
5. Thermal-error compensation
6. Remaining-useful-life estimation
7. Automatic parameter selection
8. Anomaly detection
9. Predictive maintenance
10. Quality classification

Common techniques include:

- Artificial neural networks
- Support-vector machines
- Decision trees
- Random forests
- Convolutional neural networks
- Recurrent neural networks
- Reinforcement learning
- Hybrid physics-informed models

AI models require representative and accurately labelled data. A model trained on one tool, machine or material may not perform reliably under different conditions.

14. Digital Twins for CNC Systems

A digital twin is a dynamic digital representation of a physical machine or machining process. It receives operational data and uses models to estimate, predict or optimize system behaviour.

A CNC digital twin can integrate:

- Machine geometry
- Axis positions
- Spindle condition
- Cutting-tool information
- Workpiece state
- Sensor measurements
- Process parameters
- Maintenance records

- Inspection results

Applications

- Virtual commissioning
- Collision detection
- Tool-path verification
- Process simulation
- Energy analysis
- Thermal prediction
- Predictive maintenance
- Remote monitoring
- Production optimization
- Product traceability

The value of a digital twin depends on synchronization. A static three-dimensional machine model without updated physical data is better described as a digital model than a complete operational twin.

15. Automated Metrology and Closed-Loop Manufacturing

Precision production requires measurement and correction. Traditional inspection occurs after machining, which may allow several defective components to be produced before a problem is detected.

Advanced CNC systems use:

- Touch-trigger probes
- Laser tool setters
- On-machine scanning
- Coordinate measuring machines
- Vision systems
- Surface-roughness sensors
- In-process gauging

A closed-loop quality system follows this cycle:

Machine → Measure → Compare → Compensate

Inspection data can update work offsets, tool-wear values or process parameters. This approach reduces operator intervention and prevents repeated errors.

On-machine measurement must account for machine geometry, probe calibration and temperature. A machine tool cannot automatically serve as an independent metrology instrument without appropriate uncertainty evaluation.

16. CAD/CAM and CNC Integration

Computer-Aided Design defines product geometry, while Computer-Aided Manufacturing creates tool paths and machining instructions.

Advanced CAD/CAM systems provide:

- Feature recognition
- Tool selection
- Tool-path optimization
- Collision simulation
- Cutting-time estimation
- Remaining-material analysis
- Multi-axis programming
- Post-processing
- Model-based definition

The post-processor translates a generic tool path into instructions appropriate for a particular machine and controller. Incorrect post-processing can produce axis errors or collisions even when the original CAM simulation appears correct.

17. Robotic and Hybrid CNC Systems

Industrial robots can perform machining, drilling, trimming, polishing and deburring. They offer large working areas and flexibility but generally possess lower stiffness and absolute accuracy than precision machine tools.

Hybrid manufacturing combines multiple processes in one platform, such as:

- Additive manufacturing and CNC milling
- Laser deposition and finishing
- Turning and milling
- Grinding and hard turning
- Ultrasonic assistance and cutting
- Electrical-discharge machining and milling

Hybrid systems reduce setups and allow components to be built, repaired and finished on a common platform.

18. Industrial Internet of Things and Connectivity

Connected CNC machines can exchange data with:

- Manufacturing-execution systems
- Enterprise-resource-planning systems
- Tool-management databases
- Quality-management systems
- Maintenance platforms
- Cloud and edge-computing systems

Communication standards such as MTConnect and OPC UA support structured machine-data exchange. Interoperability remains difficult because manufacturers may use different data models, protocols and proprietary interfaces.

19. Cybersecurity Challenges

Connecting CNC machines to digital networks creates cybersecurity risks. Potential attacks include:

- Unauthorized programme modification
- Theft of product designs
- Manipulation of tool offsets
- Disabling safety functions
- False sensor-data injection
- Ransomware
- Remote machine shutdown
- Alteration of quality records
- Reconstruction of confidential tool paths

A small malicious change to a tool path may create an internal defect that is difficult to detect visually.

Cybersecurity measures should include:

- Network segmentation
- Strong authentication
- Role-based access
- Programme version control
- Secure backups
- Encrypted communication
- Firmware verification
- Intrusion monitoring
- Physical access control
- Incident-response planning

20. Sustainability in CNC Manufacturing

Advanced CNC technologies can improve environmental performance by reducing:

- Scrap
- Energy consumption
- Cutting-fluid use
- Tool consumption
- Rework
- Unnecessary machine idle time
- Material removal

Energy-efficient tool paths, minimum-quantity lubrication, dry machining and condition-based maintenance can reduce environmental impact.

However, additional sensors, computers, networks and data centres consume resources. Sustainability assessments should therefore consider the entire life cycle of the manufacturing system.

21. Comparison of Conventional and Advanced CNC Systems

Feature	Conventional CNC	Advanced intelligent CNC
Process parameters	Pre-programmed	Adaptively optimized
Machine monitoring	Limited alarms	Continuous sensor monitoring
Maintenance	Preventive or breakdown-based	Predictive and condition-based
Inspection	Mainly post-process	In-process and closed-loop
Programming	Manual or basic CAM	Simulation and automatic optimization
Tool management	Operator-based	Automated identification and life prediction
Machine connectivity	Limited	Industrial network and cloud integration
Error correction	Manual compensation	Model- and data-based correction
Decision-making	Operator-dependent	AI-assisted
Production role	Automated machine	Cyber-physical manufacturing system

22. Major Implementation Challenges

22.1 High investment cost

Multi-axis machines, precision spindles, sensors, software and metrology systems require significant investment.

22.2 Shortage of skilled personnel

Advanced systems require expertise in machining, programming, robotics, electronics, data analytics and metrology.

22.3 Legacy-machine integration

Older machines may not provide standardized interfaces or sufficient computing capability.

22.4 Data quality

Missing, noisy or incorrectly synchronized data reduce the reliability of predictive models.

22.5 Interoperability

Machines, controllers and software from different suppliers may use incompatible formats and protocols.

22.6 Model generalization

AI models may perform well under training conditions but fail when the tool, material or machine changes.

22.7 Cybersecurity

Connectivity exposes production systems and intellectual property to cyber threats.

22.8 Organizational resistance

Employees may resist new systems when implementation occurs without training, consultation or clear responsibilities.

23. Challenges and Recommended Solutions

Challenge	Effect	Recommended solution
Thermal deformation	Dimensional drift	Sensors, cooling and real-time compensation
Tool wear	Poor finish and inaccurate size	Tool-condition monitoring
Chatter	Surface damage and tool failure	Stability analysis and adaptive control
Multi-axis calibration errors	Contour inaccuracies	Volumetric calibration
Data incompatibility	Weak system integration	Open communication standards
High investment cost	Slow technology adoption	Phased implementation
Skill shortage	Programming and maintenance errors	Specialized workforce training
Unreliable AI models	Incorrect predictions	Hybrid models and continuous validation
Measurement uncertainty	Incorrect compensation	Traceable calibration
Cyberattack	Machine or product manipulation	Secure industrial architecture

24. Major Findings

The study produces the following findings:

1. Advanced CNC technology improves precision through integrated mechanical, control, sensing and software capabilities.
2. Multi-axis machining reduces setups and enables complex component production.
3. Thermal deformation remains a major source of machine-tool error.
4. High-speed machining increases productivity but requires stable dynamics and advanced control.
5. Sensor-based tool monitoring can reduce unexpected failure and scrap.
6. Adaptive control enables CNC machines to respond to changing process conditions.
7. Artificial intelligence supports prediction, but its reliability depends on representative data.
8. Digital twins improve simulation, monitoring and traceability when synchronized with physical machines.
9. In-process metrology enables closed-loop quality control.
10. Connectivity improves production coordination but creates cybersecurity risks.
11. Advanced equipment cannot independently ensure precision without calibration, process planning and skilled operation.
12. Future CNC systems will become increasingly autonomous and self-correcting.

25. Recommendations

1. Conduct geometric and volumetric calibration at planned intervals.
2. Use temperature sensing and thermal-error compensation.
3. Integrate tool-condition and vibration monitoring.
4. Validate CAM programmes and post-processors before machining.
5. Introduce multi-axis technology according to actual product requirements.
6. Establish traceable in-process and post-process metrology.

7. Adopt interoperable industrial communication standards.
8. Validate AI models across multiple tools, materials and operating conditions.
9. Maintain human supervision for safety-critical decisions.
10. Protect CNC systems through industrial cybersecurity controls.
11. Train employees in programming, metrology, automation and data analysis.
12. Implement digital twins gradually, beginning with high-value use cases.
13. Measure productivity through quality, tool life and downtime—not cycle time alone.
14. Integrate sustainability objectives into machining-process planning.
15. Use closed-loop inspection to prevent repeated production errors.

26. Future Scope

Future CNC research is expected to focus on:

- Self-optimizing machining
- Physics-informed artificial intelligence
- Autonomous process planning
- Explainable machine-learning models
- Grid- and cloud-connected machine tools
- Human–robot collaborative machining
- Digital-thread integration
- Intelligent remanufacturing
- Self-calibrating machines
- Secure edge computing
- Zero-defect manufacturing
- Sustainable tool-path optimization

The future CNC machine will combine physical precision with computational intelligence, allowing it to predict errors and modify its operation before defective production occurs.

27. Conclusion

Advanced CNC technologies are essential for producing high-quality components with complex geometry and tight tolerances. Multi-axis motion, high-speed machining, intelligent controllers, process sensors, adaptive control, artificial intelligence, digital twins and automated inspection have expanded the capabilities of conventional machine tools. Precision depends on the complete manufacturing system rather than the CNC machine alone. Machine geometry, thermal conditions, spindle behaviour, tool wear, fixture design, material variation, control accuracy and measurement uncertainty interact to determine final component quality. Advanced technology can improve productivity and reduce scrap, but implementation requires skilled personnel, reliable data, calibration, cybersecurity and integration with production-management systems. Manufacturers should adopt these technologies according to measurable production needs rather than treating digitalisation as an objective by itself. As CNC systems become more connected and intelligent, precision manufacturing will increasingly move toward autonomous, closed-loop and self-correcting production. Human expertise will remain important for defining objectives, validating decisions and ensuring safe and responsible operation.

References

- [1] Altintas, Y. (2012). *Manufacturing Automation: Metal Cutting Mechanics, Machine Tool Vibrations, and CNC Design* (2nd ed.). Cambridge University Press. <https://doi.org/10.1017/CBO9780511843723>
- [2] Denkena, B., & Denkena, B. (Eds.). (2013). *Cyber-Physical and Intelligent Systems in Manufacturing and Life Cycle*. Academic Press. <https://doi.org/10.1016/C2012-0-01239-7>
- [3] Kritzinger, W., Karner, M., Traar, G., Henjes, J., & Sihn, W. (2018). Digital twin in manufacturing: A categorical literature review and classification. *IFAC-PapersOnLine*, 51(11), 1016–1022. <https://doi.org/10.1016/j.ifacol.2018.08.474>
- [4] Mayr, J., Jedrzejewski, J., Uhlmann, E., Donmez, M. A., Knapp, W., Härtig, F., Wendt, K., Moriwaki, T., Shore, P., Schmitt, R., Brecher, C., Würz, T., & Wegener, K. (2012). Thermal issues in machine tools. *CIRP Annals*, 61(2), 771–791. <https://doi.org/10.1016/j.cirp.2012.05.008>
- [5] Teti, R., Jemielniak, K., O'Donnell, G., & Dornfeld, D. (2010). Advanced monitoring of machining operations. *CIRP Annals*, 59(2), 717–739. <https://doi.org/10.1016/j.cirp.2010.05.010>
- [6] Möhring, H. C., Wiederkehr, P., Erkorkmaz, K., & Kakinuma, Y. (2020). Self-optimizing machining systems. *CIRP Annals*, 69(2), 740–763. <https://doi.org/10.1016/j.cirp.2020.05.007>
- [7] Schmitz, T. L., & Smith, K. S. (2019). *Machining Dynamics: Frequency Response to Improved Productivity* (2nd ed.). Springer. <https://doi.org/10.1007/978-3-319-93707-6>
- [8] Tao, F., Zhang, M., Liu, Y., & Nee, A. Y. C. (2019). Digital twin driven prognostics and health management for complex equipment. *CIRP Annals*, 68(1), 169–172. <https://doi.org/10.1016/j.cirp.2019.04.055>
- [9] Tao, F., Cheng, J., Qi, Q., Zhang, M., Zhang, H., & Sui, F. (2018). Digital twin-driven product design, manufacturing and service with big data. *The International Journal of Advanced Manufacturing Technology*, 94, 3563–3576. <https://doi.org/10.1007/s00170-017-0233-1>
- [10] Wang, L., Törngren, M., & Onori, M. (2015). Current status and advancement of cyber-physical systems in manufacturing. *Journal of Manufacturing Systems*, 37, 517–527. <https://doi.org/10.1016/j.jmsy.2015.04.008>
- [11] Gao, R., Wang, L., Teti, R., Dornfeld, D., Kumara, S., Mori, M., & Helu, M. (2015). Cloud-enabled prognosis for manufacturing. *CIRP Annals*, 64(2), 749–772. <https://doi.org/10.1016/j.cirp.2015.05.011>
- [12] Grzesik, W. (2017). *Advanced Machining Processes of Metallic Materials* (2nd ed.). Elsevier. <https://doi.org/10.1016/C2013-0-16337-1>
- [13] ISO. (2012). *ISO 230-1:2012—Test Code for Machine Tools: Geometric Accuracy of Machines Operating Under No-Load or Quasi-Static Conditions*. [ISO standard](#)
- [14] ISO. (2007). *ISO 230-3:2007—Test Code for Machine Tools: Determination of Thermal Effects*. [ISO standard](#)
- [15] National Institute of Standards and Technology. (2024). *Smart Manufacturing Systems Design and Analysis Program*. [NIST](#)